

SFM-AT200



The SFM-AT200 is compatible with every LPBF-printer on the market.



Compact depowdering unit for powder removal of metal laser-melted parts

The SFM-AT200 cleans metal laser-melted parts within a sealed process chamber, with targeted vibration and automated rotation.

Due to rotation of the parts, including the build plate, unmelted build material is removed from complex voids and support structures.

The compact design of the SFM-AT200 optimizes the footprint as well as the consumption of inert gas.

The internal stainless steel design makes the SFM-AT200 the ideal cleaning system for medical components with high cleaning requirements. The depowdering system is based on the unique Solukon Smart Powder Recuperation® technology.



System specifications

Installation space (W x D x H)	2,200 x 2,400 x 2,200 mm
Weight	150 kg
Mains voltage / frequency	400 / 50 - 60 V / Hz
Power consumption	0.4 kW
Power supply	16 A

Compressed air specifications

Working pressure	6 bar
Consumption	max. 300 l/min

Inert gas specifications*

Working pressure	6 bar
Consumption	max. 300 l/min

* only with inert gas infusion option

Part spectrum

- material: aluminum-, steel-, titan- or copper alloy
- weight: up to 60 kg
- dimensions: up to 300 x 300 x 230 mm³

Basic features

- automated rotation device
- turntable for manual positioning of the parts
- powder lock with special container
- vibration mechanism with wide frequency range

Options

- dust removal for non-reactive materials
- inert gas infusion for reactive materials (ATEX)
- direct link to sieving station

Advantages

- certified explosion protection
- high degree of protection from harmful dusts
- fast and economic part cleaning
- comfortable part handling
- qualifiable and reproducible cleaning results