


# INTRODUCING THE NEW POWERSHOT PERFORMANCE SERIES

Next level blasting systems purposebuilt for the factory of the future & high-volume production with Additive Manufacturing



#### REDEFINING THE STANDARD OF

#### INDUSTRIAL CLEANING AND SURFACING





#### POLYSHOT CLEANING (PSC) NEW /



- ✓ Proprietary cleaning process with plastic blasting media
- ✓ Gentle and efficient powder removal
- ✓ Allowing for a wider range of process parameters and precision adjustment than conventional cleaning processes
- ✓ Compatible with all common powder-bed technologies and improved depowdering of process challenging materials (e.g. TPU)
- ✓ Developed for the P2P Workflow: The residuefree cleaning process for brilliant colors







#### **POLYSHOT SURFACING (PSS)**

- ✓ Proprietary surfacing process with plastic beads
- ✓ Most efficient surfacing technology to achieve end-use parts
- √ Non-abrasive surface homogenization
- ✓ Semi-glossy surfaces with ideal properties: The foundation for superior coloring results
- ✓ Achieves high scratch resistance and soft haptics





### TAKING THE PRINT-TO-PRODUCT WORKFLOW TO THE NEXT LEVEL







The Powershot Performance Series is designed for the most demanding applications within AM. The first system with a wide multi belt has an effective process volume of 55 liters and can handle 10kg of parts. While being able to process a full-sized build job, the Powershot Performance series has the smallest workspace requirements on the market. The blasting media sieving and separation

unit leads to a lower consumable consumption and results in a reduction of costs. With a short cycle time and a capacity of a full-sized build job per run, the Powershot Performance series is more efficient than any other system available. Complemented by both our proprietary Cleaning & Surfacing processes these systems are designed for high volume production.

CAPACITY

PROCESS TIME

**>** 

Up to

1.5x

Reduce up to

20%

**EFFICIENCY** 

Increase up to

2x EFFICIENCY



## Ready to form the factory of the future - now

Our Powershot Performance series blends right into the factory of the future with state-of-the-art automation technology from Siemens. Integrated into your digital shopfloor with ERP/MES connectivity and standardized communication protocols like OPC-UA. Monitor and analyze all data surrounding the state and condition of the systems for performance & process optimization (with standardized IIoT messaging protocols like MQTT). Via a secure & certified VPN connection the systems can be accessed remotely for maintenance and troubleshooting to increase system uptime. This ultimately results in an unmatched performance of your production lines.

## Setting the stage for automation in Additive Manufacturing

All three versions of the Powershot Performance Series provide an intuitive user-friendly interface with optional user-levels. Pre-installed programs with specifically developed process parameters can be controlled. Your individual process parameters can be configured and saved easily, enabling a fast adaption to each specific application. Automatic part handling such as automatic unloading of your processed parts supports the integration into the DyeMansion Print-to-Product Workflow and the compete Additive Manufacturing chain. The design of the system allows for upcoming extension features for automatic loading.





#### **TECHNICAL DATA**



**AUTOMATION** Individual programming, control and monitoring of process parameters via touch screen. Fully automatic

unloading of processed parts.

**PERFORMANCE** 

Cycle time Individually configurable,

typically 3 to 15 minutes each process

Capacity per run Full sized build job

(e.g. full EOS P396 or 1.5x HP Jet Fusion 4200/5200)

55 liters | 14.5 gal Effective volume of multi belt

Effective dimensions of multi belt (L x W x H) 409mm x 800mm x 325mm | 12.2 inch x 31.5inch x 12.8inch

**DIMENSIONS** 

System (L x W x H)

Recommended space requirement

in operation (L x W x H)

External extraction unit1 (L x W x H)

Recommended space requirement

in operation (L x W x H)

1630mm x 2205mm x 2097mm | 64,2inch x 86,8inch x 82,6inch 2530mm x 2900mm x 2600mm | 99.6inch x 114.2inch x 98.4inch

1000mm x 800mm x 2000mm | 39.4inch x 31.5inch x 78.7inch

1500mm x 1300mm x 2000mm | 55.1inch x 51.2inch x 78.7inch

**POWER** 

Supply From 1.2kW up to 2.0kW Requirements 400V. 50Hz. 16A

**COMPRESSED AIR** 

Consumption<sup>2</sup>

Minimum: 1.4m3/min at 2.2bar | 49cfm at 32psi Maximum: 1.8m3/min at 5bar | 64cfm at 73psi

**CERTIFICATION<sup>3</sup>** 

CE | 2006/42/EG EMV | 2014/30/EU RoHs | 2011/65/EU

DyeMansion North America Inc. 4020 S. Industrial Drive, #160 Austin, TX, 78744 United States of America

+1737 205 5727 hello@dyemansion.com

For more information, visit: www.dyemansion.com



Robert-Koch-Strasse 1 82152 Planegg-Munich Germany +49 89 414 170 500 hallo@dyemansion.com



#### **AVAILABILITY**

The Powershot Performance Series will be rolled out with selected pilot customers. Series systems can be ordered as of 03 2022.

<sup>&</sup>lt;sup>1</sup> External extraction unit required if no in-house extraction available.

<sup>&</sup>lt;sup>2</sup> To ensure that the machines are fully functional, DyeMansion recommends to configure the compressed air system for maximum consumption.

<sup>&</sup>lt;sup>3</sup>Deviations possible depending on system variant.

#### **CUSTOMER VOICES**

"We have superior surfaces with PolyShot Surfacing. That was proven when we approached customers with injection molded parts, and they said they liked the PolyShot surface even better."

KONSTANTIN BRUNNBAUER
VP of Production

"With PolyShot Surfacing our earrings lose their roughness and get a unique, matt-glossy, and high-quality look as well as the pleasant wearing comfort."

MARIE BOLTENSTERN
CEO & Head of Design



**PROGLOVE** 

# END-USE PARTS WITH SUPERIOR COLORING RESULTS

